

Style Specifications (Sales Department)

A & G INCORPORATED

Print : 8/16/2007 9:09:14AM

1501 EAST CERRITOS AVENUE, ANAHEIM, CA 92805, Phone: 714-765-0400, Fax: 714-765-0450

By : bonnied

1701	AAA Ringspun Tee	Fabric : 27 20/1 100% COTTON KRS 5.5 OZ	5.50 OZ
		Trim : R27 20/1 100% COTTON KRS 6 OZ	

Customer :	Customer Proto # :
------------	--------------------

Component	Component Description	S	M	L	XL	2XL	3XL			Tol (+/-)
1	BDW Body Width (1" Below Armhole)	18	20	22	24	26	28			1
2	BDL Body Length (HPS to Edge)	27	29	31	32	33	34			1
3	NOP Neck Opening (Seam to Seam)	6 1/2	6 1/2	7	7	7 1/2	7 1/2			1/2
4	COW Collar Height (Set In)	3/4	3/4	3/4	3/4	3/4	3/4			1/8
5	SHW Shoulder Width (Seam to Seam)	17	19	21	23	25	27			1/2
6	BSH1 Bottom & Sleeve Hem 1/4" DN	3/4	3/4	3/4	3/4	3/4	3/4			1/8
7	AOS Armhole STRAIGHT(No Binder)	8 3/4	9 3/4	10 3/4	11 1/2	12 1/2	13 1/2			1/2
8	UPL Upper Sleeve Length (No Cuff)	7 3/4	8 1/4	9	9 1/2	9 1/2	10			1/2
9	SOP Sleeve Opening (Relaxed)	6 1/2	7	7 1/2	8	8 1/2	9			1/2

Construction Details : **ZZYZZZZZZZZL**

Set In Collar-Rib Fabric

NO Coverstich at Neck

Close Cllr-3/4"Towards the Bk(Lft as Worn)T+/-1/4"

Shoulder To Shoulder Tape-Self-Fabric

DbI-Ndl Hem Sleeves & Bottom-1/4" Gauge Spacing

Bttm Hm Fnshd-Match Back@1 1/2"-2"(RghtasWorn)

Label Instructions :

AAA (Black Label)

Tear-away tag (Alstyle Supply)

Miscellaneous :

Stiches per Inch : Dye Process : Comp/1/4 Turn/Pc-dyed

Thread Desc. : Stdrd Fabric Finish : 1/4 Turned-Tubular

Revision :

Approved By : _____

Approved Date : _____